

























Technical specifications

Eternal meets the requirements of ISO 10582 and EN 649

	Total Thickness	ISO 24346 / En 428	2.0 mm
	Wear layer thickness	ISO 24340 / EN 429	0.7 mm
	AUS/NZ Collection size		42
	Commercial use	ISO 10874 / EN 685	34 very heavy
	Industrial use	ISO 10874 / EN 685	43 heavy
	Roll width	ISO 24341 / EN 426	2.00 m
	Roll length	ISO 24352 / EN 426	± 25 m
	Total weight	ISO 23997 / EN 430	2.8 kg/m ²
	Dimensional stability	ISO 23999 / EN 434	< 0.1 %
	Residual indentation	ISO 24343-1 / EN 433	≤ 0.05 mm
	Abrasion resistance	EN 660-2	group T
	Castor chair continuous use	ISO 4918 / EN 425	no effect
	Light Fastness	ISO 105-BO2	≥ 6
	Flexibility	ISO 24344 / EN 435	Ø 10 mm
	Resistance to chemicals	ISO 26787 / EN 423	very good
	Reaction to fire	EN ISO 9239-1	CRF/CHF: 8.4kW/m ² Smoke Development: 203%min
	Slip resistance	AS/NZS 4586:2004	R10
	Electrical resistance	EN 1081	R1 > 1.10 ⁹ Ω
	Suitable for heating	AS 1157.4: 1978	Yes*
	Wetroom certification	EN 13553	Yes
All Eternal products meet the requirements of EN 14041			
	Reaction to fire	EN 13501-1	B _s s1
	Slip resistance	EN 13893	DS - μ ≥ 0.30
	Body voltage	EN 1815	≤ 2 kV
	Thermal conductivity	EN 12524	0.25 W/m-K

*Temperature < 30 °C

The quality and environmental management systems of Forbo Coevorden (NL) where Forbo Eternal is manufactured are certified in accordance with ISO 9001 and ISO 14001



Recommended Adhesives

Our recommended adhesive for the Eternal collection is Forbo Fix 540. Please contact customer services for further information.



Service products

As a total solutions provider, Forbo offers a collection of products to complement the installation, finishing and maintenance of our products. An optimal assortment of adhesives, welding rods, subfloors and installation tools can be offered. To give the floor the finishing touch, we provide a collection of skirtings, profiles and stair nosings.