

# DOT 322



1 x 18W  
TC-D/E  
(4 pin)



1 x 18W  
TC-T/E  
(4 pin)



## OPTIONS

/02		Polished Silver Reflector IP20	/03		Satin Silver Reflector IP20
-----	--	--------------------------------	-----	--	-----------------------------

**AXLOCK ACCESSORIES** Fitted to downlight after installation.  
Accessory trims available White /01 or Silver /55.

A28		Round Ceiling Plate IP20	A7-FT		Convex Frosted Lens IP54
A7-CL		Convex Clear Lens IP54	A10-FG		Round Flush Glass IP54
A7-FR		Convex Fresnel Lens IP54	A11		Round Halo Glass IP20
A10-DG		Round Dropped Glass IP20			

White Ceiling Plate A28/01 and Satin Silver Reflector /03 fitted to downlight as standard.

Electronic Ballast	1 x 18W	HF
Lampholder	1 x G24q-2 (4 pin) or GX24q-2 (4 pin)	
Total system energy consumption $P_L(W)$		21W
Weights	Luminaire	490 gms
	Remote Gear	360 gms
IEC 60598.1.2		Complies
AS/NZS 60598.1.2		Complies
IP Rating:		Refer Accessory
Magnetic Low Loss Option Available		LL
Lampholder	1 x G24d-2 (2 pin) or GX24d-2 (2 pin)	
Total system energy consumption $P_L(W)$		24W
Weight	Luminaire with Integral Gear	756 gms

## ORDERING CODE FORMAT

Example:	DOT	322	/03	/LL	/FTB	/A28	/FP	/L-40
Model Number								
Reflector Option								
Control Gear Type								
Fused Terminal Block								
Accessory Code								
Flex and plug								
Complete with Lamp (state colour /30-830 or /40-840)								

