

Ceiling Speakers



100mm & 200mm Recessed



Notifier Inertia Fire Systems 100V, 5 watt flush mount ceiling speakers with 5 selectable power settings, come in 100mm and 200mm diameter models.

One-Shot Recessed



Notifier Inertia Fire Systems "One-Shot" easy fit recessed ceiling speakers, snap fit to any 10mm - 13mm thickness ceiling by means of the integral pressure clips.

Surface Mount



Notifier Inertia Fire Systems surface mount 100mm speaker is easy to fit and aesthetically pleasing in design.

Auckland +649 623 5050

Brisbane +617 3391 5777

Melbourne +613 9421 5552

Sydney +612 9899 4155

Perth +618 9270 6555

www.notifier.com.au

Ceiling Speakers



These speaker units have been engineered to meet the demanding requirements of the relevant Australian Standard.

All models come standard with patented transformer safety cover and cable restraint mechanisms.

This cover also eliminates the possibility of short circuits occurring from contact with the likes of air conditioning ducts.

All models come with a 4 way wire protect terminal and 22 μ f bipolar capacitor in accordance with the Australian Standard.

The transformers are wound on professional grade grain oriented steel cores for extended frequency response.

The speaker drivers have been chosen for optimum frequency response and efficiency for background music, paging and EWIS applications.

Specifications:

Voltage:	100V
Impedance:	8 ohm
Output Power:	0.33W, 0.6W, 1.25W, 2.5W, 5W
Sound Pressure Level:	92dB (1W @ 1m)
Connection:	4 way terminal block plus 22 μ f bipolar capacitor

Cat.70.07.02

Auckland +649 623 5050

Brisbane +617 3391 5777

Melbourne +613 9421 5552

Sydney +612 9899 4155

Perth +618 9270 6555

www.notifier.com.au

© 2004 Honeywell Ltd t/a Notifier Inertia. The manufacturer reserves the right to change designs or specifications without obligation or without further notice